

FUZE WASH 250



250W Full Spectrum RGBMA LED Wash Fixture



KEY FEATURES

250W Full Spectrum RGBMA LED Engine

Up to 8500 Total Lumen Fixture Output @ 6500K

CRI up to 92

Wide Zoom Range from 6° to 50°

CMY Emulation

Virtual Color Correction

Green/Magenta Shift

Virtual Gel Swatch Book

NFC & Aria x2 Wireless Device Management

The **FUZE WASH 250™** is a powerful automated LED Fresnel wash fixture designed for theater, television, events and a wide array of other precision lighting applications. A High-CRI engine utilizes a 5-color homogenized LED array consisting of Red, Green, Blue, Mint, and Amber sources. The carefully tuned LEDs ensure accurate color reproduction while delivering a powerful output of up to 8500 lumens and maximum CRI of 92. Virtual color temperature, Magenta / Green adjustment plus CMY or RGB emulation provide the designer with immediate access to the impressive LED color array.

The **FUZE WASH 250** is designed for any application where an automated Fresnel fixture with outstanding and impactful colors, a wide zoom range and a soft field is required.



FUZE WASH 250



250W Full Spectrum RGBMA LED Wash Fixture

SPECIFICATIONS

SOURCE

250W 6,500K RGBMA (Red, Green, Blue, Mint, Amber) LED Engine

30,000 Hour Average LED Life*

*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

PHOTOMETRIC DATA

8500 Total Lumen Fixture Output

CRI 92

Zoom Range 6° - 50°

Field Angle 13.9° - 55.8°

Beam Angle 8.4° - 43.6°

EFFECTS

Motorized Zoom

Variable 16-bit Dimming Curve Modes

High Speed Electronic Shutter and Strobe

COLOR

RGBMA Color Array

CMY and RGB Emulation

Variable CCT 2400K - 8500K

Green/Magenta Shift

Virtual Gel Swatch Book

CONTROL / CONNECTIONS

Standard, Extended, RGB, RGB Extended, CMY, & CMY Extended DMX Channel Modes

16-bit Pan, Tilt, and Dimming Control

DMX Adjustable LED Frequency

4 Button Touch Control Panel

Full Color 180° Reversible LCD Menu Display

DMX, RDM, Art-Net, sACN Protocol Support

Aria x2 Wireless Device Management

NFC Configuration

Locking 5pin XLR Connector In/Out

Locking IP65 Power Connector In/Out

RJ45 Ethernet In/Out (Art-Net & sACN)

SIZE / WEIGHT

Length: 8.2" (208mm)

Width: 12.9" (327mm)

Vertical Height: 18.1" (459mm)

Vertical Height w/ Snoot: 19.4" (493mm)

Weight: 24.8lbs. (11.3kg)

ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz

Max Power Consumption 350 W

14°F to 113°F (-10°C to 45°C)

APPROVALS / RATINGS

CE | cETLus | IP20 | FCC



ORDERING INFORMATION

SKU (USA)	SKU (EU)	ITEM
FUZ754	1237000396	Fuze Wash 250



Specifications are subject to change without notice ©Elation Professional 05/13/2026
Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

FUZE WASH 250



250W Full Spectrum RGBMA LED Wash Fixture

UNIT DIMENSIONS

